





1998

Lighter, faster and even more exhilarating

Integratyper.org





THE SIZE OF A BANTAMWEIGHT,

Thanks to numerous refinements, the VTEC engine in the Type-R produces an incredible 195 horsepower from just 1.8 liters — giving it the highest output per liter of any normally aspirated automobile powerplant offered in the United States.



195-HORSEPOWER VTEC ENGINE (25-HP INCREASE OVER INTEGRA GS-R)

- Large-diameter throttle body and single-port intake manifold to maximize high-rpm engine efficiency
 - Hand-polished intake ports to improve engine airflow
- Increased-duration, higher-lift camshafts for improved engine breathing <
- 12 percent lighter intake valves to extend engine rev range to 8400 rpm
 - High-compression (10.6:1), low-friction pistons
- Forged-steel crankshaft with eight counterweights to reduce vibration at high rpm
 - Large-diameter, free-flow intake and exhaust systems <
 - Aluminum oil cooler maintains optimum engine-oil temperature

HIGH-PERFORMANCE COCKPIT

- Deeply bolstered, high-traction racing-design front seats with suede-like side trim <
 - Leather-wrapped steering wheel and gearshift knob <
 - Carbon fiber-look instrument panel <
 - Numbered plaque affixed to center console denotes limited-edition status



IMPROVED RESPONSIVENESS AND HANDLING

- > Lightweight flywheel for improved throttle response
- > Close-ratio, five-speed gearbox provides smooth, seamless shifting
- > Heavy-duty, hydraulically actuated clutch for reliable, positive shift action
- Torque-sensitive, helical limited-slip differential improves traction and enhances responsiveness in high-cornering-load situations
- Lower suspension, stiffer springs and firmer shocks
- > Larger-diameter front and rear disc brakes (vented front discs)
- High-performance 195/55 R15 Bridgestone Potenza RE010 summer-use tires on lightweight, five-bolt 6.0 JJ x 15 alloy wheels
- Reduced vehicle weight (79 pounds lighter than Integra GS-R)

BODY/STRUCTURAL ENHANCEMENTS

- > Stiffened body structure for exceptional rigidity and suspension control
- High rear wing for added stability
- Chin spoiler for improved aerodynamics

A TACHOMETER THAT

peak redling in the deliver performs fast reason built

With its 8000-rpm power peak and sizzling 8400-rpm redline, the VTEC engine in the Integra Type-R delivers the exhilarating performance and lightning fast response normally associated with purposebuilt racing powerplants.

To put it bluntly, the Acura Integra Type-R is not for everyone. This is a sports coupe created exclusively for those demanding driving enthusiasts



who insist on nothing less than no-compromises performance. To that end, the Type-R features a wealth of mechanical refinements, including a specially prepared VTEC engine rated at 195 horsepower (a 25-hp increase over the Integra GS-R); a firm, sport-tuned suspension; high-performance summer-use tires;

DESIGNED FOR DEMANDING ENTHUSIASTS, THE TYPE-R COMBINES

A LIGHTWEIGHT DESIGN WITH HIGH-PERFORMANCE COMPONENTS - CREATING AN INTEGRA

OF UNPRECEDENTED POWER AND RESPONSE.

a close-ratio five-speed gearbox; a limited-slip differential; large-diameter front-disc brakes; and a cockpit



carefully designed for maximum efficiency at the wheel. The result is a sporting automobile of exceptional purpose and prowess, a car all but unrivaled in its class. No wonder that the RealTime/Comptech Integra Type-R race car

captured the T2-class drivers' title in the highly competitive 1997 SCCA World Challenge. Because the Acura Integra Type-R doesn't just set the sports-coupe standard; it sets the pace, too.

INSPIRED BY A PROUD HERITAGE OF RACING

SUCCESS, THE TYPE-R IS THE MOST THRILLING

INTEGRA EVER BUILT. A true driver's car, the Type-R

enhances the reputation for race-



bred performance and razor-sharp responsiveness for

which the Acura Integra is justly renowned.

TYPE-R ENGINEERING FEATURES

- > 195-horsepower, 1.8-liter, 16-valve, DOHC, in-line 4-cylinder engine
- > High-volume intake manifold, hand-polished intake ports
- > Twin-coil intake valve springs with oval cross-section for high lift
- > Lightweight, high-flow intake valves
- > High-lift, high-strength camshafts
- > Lightweight, high-strength connecting rods
- > High-rigidity, 8-counterweight crankshaft
- > High-compression, low-friction pistons
- > High-volume airbox with repositioned intake
- > High-flow exhaust system
- > Torque-sensitive helical limited-slip differential
- >15 mm lower suspension with 70% larger rear stabilizer bar, revised caster and camber settings, and harder bushings
- > Increased diameter disc brakes
- > Front suspension aluminum tower bar
- > Rear suspension performance brace

SPECIFICATIONS

1.8-liter, 16-valve, DOHC, in-line ENGINE TYPE

4-cylinder

REDLINE 8400 rpm FUEL CUTOFF 8500 rpm

HORSEPOWER, SAE NET 195 hp @ 8000 rpm 130 lbs-ft @ 7500 rpm TORQUE, SAE NET

3.19 in x 3.43 in (81 mm x 87.2 mm) BORE & STROKE

1797 cc (110 cu in) DISPLACEMENT

COMPRESSION RATIO

INDUCTION SYSTEM Programmed Fuel Injection

(PGM-FI) with single-port intake

manifold

VALVETRAIN 4 valves per cylinder, dual overhead

> camshafts driven by a single belt with Variable Valve Timing and Lift

Electronic Control (VTEC)

ENGINE BLOCK Aluminum alloy with cast-in iron

cylinder liners

CYLINDER HEAD Aluminum alloy

EMISSION CONTROL 3-way catalytic converter/EACV IGNITION SYSTEM RECOMMENDED FUEL STABILIZER BARS

Rear Discs

Electronic ignition with knock sensor Premium unleaded, 91 octane

> Front Ball joint type 0.94 in diameter

> > 0.87 in diameter

STEERING TYPE Variable power-assisted, rack-andpinion with rotary-valve steering gear

STEERING RATIO

WHEELS 6.0 JJ x 15 cast-aluminum alloy TIRES Bridgestone Potenza RE010

Rear

195/55 R15 84V*

BRAKING SYSTEM Dual-diagonal, power-assisted,

4-wheel disc brakes with ABS

Ventilated, 11.1 in (282 mm) diameter, Front Discs

0.98 in (25 mm) rotor thickness

Solid, 10.2 in (260 mm) diameter, 0.39 in (10 mm) rotor thickness

POWERTRAIN

TYPE Transverse-mounted front engine/ front-wheel drive with equal-length halfshafts TRANSMISSION Ratios (:1)

3.230 1st 2.105 2nd 3rd 1.458 4th 1.107 5th 0.848 Reverse 3.000 Final Drive 4.400

COMFORT AND CONVENIENCE

- > Air conditioning (optional)
- > Power windows
- > Power door locks
- > AM/FM stereo/CD with 6 speakers and power antenna

INTERIOR FEATURES

- > Type-R-exclusive upholstery combination
- > Driver's seat lumbar adjustment
- > Leather-wrapped steering wheel and gearshift knob
- > Amber instrument illumination

> Center console with armrest and Type-R numbered plaque

> Type-R-exclusive ignition key

EXTERIOR FEATURES

- > White-finished, 5-lug, lightweight aluminum-alloy wheels
- > Wing-type rear spoiler
- > Type-R decals/emblems
- > Body-colored front chin spoiler, side sills, front and rear bumpers
- > Projector beam headlights (low beams)
- > Dual power door mirrors
- > Exclusive Championship White exterior finish

SAFETY FEATURES

- > 4-wheel Anti-Lock Braking System (ABS)
- > Driver's and front passenger's air bag Supplemental Restraint System (SRS)
- > Side-impact door beams and hip pads
- > 3-point outboard seat belts
- > 5-mph bumpers (front/rear)
- > Front and rear crumple zones
- > Rear window wiper

EXTERIOR DIMENSIONS

WHEELBASE		101.2 in	(2570 mm)
TRACK	Front	58.3 in	(1480 mm)
	Rear	58.1 in	(1475 mm)
LENGTH		172.4 in	(4380 mm)
WIDTH		67.3 in	(1710 mm)
HEIGHT		50.2 in	(1275 mm)
MINIMUM GROUND			
CLEARANCE		4.5 in	(115 mm)
CURB WEIGHT		2595 lbs	(1177 kg)
WEIGHT DISTRIBUTION		% front/rear	62/38

TYPE-R ACCESSORIES

- > Air conditioning kit > Trunk mat > Floor mats
- > Simulated carbon-fiber shift knob
- > Nose mask

WARRANTIES

Vehicle 4-year/50,000-mile limited warranty

Outer Body Rust-Through 5-year/unlimited-mile limited warranty Roadside Assistance (TLC) 4-year/50,000-mile



^{*}The unique high-performance tires on this vehicle will wear more rapidly than normal passenger car tires. The life may be significantly less than 10,000 miles, depending upon driving conditions. This tire's high-performance tread pattern is also not designed for winter driving. Driving in snow and on ice should be avoided. © 1998 Acura Division of American Honda Motor Co., Inc., Acura, Integra and VTEC are trademarks of Honda Motor Co., Ltd. Specifications, features, illustrations and equipment shown in this existalog are based upon the latest available information at the time of publication. Although descriptions are believed to be correct, accuracy cannot be guaranteed. American Honda Motor Co., Inc., reserves the right to make changes at any time, without notice or obligation, in colors, specifications, accessories, materials and models. See the Acura Integra Accessories brochure for a full list of optional equipment. Call 1-800-TO-ACURA/www.acura.com for the dealer nearest you.

Make an intelligent decision. Buckle up.

